

## Digital Model, with timer and heater

### Characteristics:

1. Use ordinary tap water, alcohol or solvent as cleaning;
2. High power transducer cleaning effect significantly, usable macroscopic observation;
3. After cleaning objects shine light;
4. Digital LCD control boot time;
5. The stainless steel shell, bladder and cover, more upscale;
6. Waterproof properties is greatly improved, more safety products last;
7. With constant temperature system with heating;
8. The stainless steel ultrasonic cleaning basket (optional).



### Main Technical Parameters:

Model	FSF-010S	FSF-020S	FSF-030S	FSF-031S	FSF-040S	FSF-060S	FSF-080S	FSF-100S
Frequency	40KHz							
Timer	0-30 min							
Heater	RT-80°C							
Transducer(PCS)	1	2	3	3	4	6	8	10
Capacity	2L	3.2L	4.5L	6.5L	10L	15L	22L	30L
Ultrasonic Power(W)	80	120	180	180	240	360	480	600
Heating Power	100W	100W	150W	150W	200W	300W	400W	500W
Tank size (L*W*H MM)	150*135*100	240*135*100	300*150*100	300*150*150	300*240*150	300*300*150	500*300*150	500*300*200
Unit Size (L*W*H MM)	175*160*210	265*165*220	325*180*220	325*180*280	325*265*280	500*325*280	360*325*280	500*325*320
G.W/N.W	2.8/2.4	4.3/3.6	5.4/4.6	6.2/5.4	8.4/7.3	10.3/9.1	14/12.6	16/14.4

## Power Adjustable Model, with timer and heater

### Characteristics:

1. SUS304 stainless steel liner material, mold stamping no welding;
2. The liner thickness of 1.1mm(welcome with a caliper measurement) thicker type, longer service life;
3. Heating automatic constant temperature system, 20-80 ° C can be set freely.
4. Digital control working hours, 1-30 minutes can be freely set.
5. Double insurance switch power supply socket, safe and secure.
6. The standard electric power line using industrial grade, bold power line, heat resistance, resistance to softening.
7. Power 144-360W adjustable, light wash or heavy wash can be controlled according to the characteristics of the products.

### Main Technical Parameters:

Model	FSF-040ST	FSF-060ST	FSF-080ST	FSF-100ST
Frequency	40KHz			
Timer	0~30 min			
Heater	20°C~80°C			
Transducer	4PCS	6PCS	8PCS	10PCS
Capacity	10L	15L	22L	30L
Heating Power	200W	300W	400W	500W
Ultrasonic Power(W)	96~240	144~360	192~480	240~600
Tank size (L*W*H MM)	300*240*150	330*300*150	500*300*150	500*300*150
Unit Size (L*W*H MM)	325*265*280	330*325*285	530*325*285	530*325*325

